



## 2/2-el.mag.vent.,NC,vod. krm.,230-240V,50-60Hz,NBR,G3/8,0.2-16bar

Kategorija: [Solenoid valve, NC, pilot-operated](#)  
Šifra: **102915RIE**

(slika je simbolična)

### Kratek opis

2/2-way solenoid valve brass, NC, pilot operated, 230-240V, 50-60Hz, 16VA, Medium temp. -10°C to 90°C, NBR, G 3/8, PN 0.2 - 16bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Električni priključek	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 3/8
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	NBR
Min. obratovalni tlak [bar]	0.2
Vrsta	4
DN	13
Max. obratovalni tlak [bar]	16
A [mm]	54.0
B [mm]	60.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	90