



2/2-el.mag.vent.,NC,vod. krm., 24V DC,8W,NBR,G1/2,0.1-10bar

Kategorija: [Solenoid valve, NC, pilot-operated](#)
Šifra: **102937RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve brass, NC, pilot operated, 24V DC, 8W, Medium temp. -10°C to 90°C, NBR, G 1/2, PN 0.1 - 10bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Min. sobna temperatura [°C] | -10 |
| Min. temperatura medija [°C] | -10 |
| Električni priključek | For connector socket Pg 9/Pg 11 acc. to ISO 4400 |
| Ffunkcija | normally closed (NC) |
| IP zaščita | IP 65 (with connector socket fitted) |
| Navoj | G 1/2 |
| Notranji deli | Stainless steel |
| Ohišje | Brass |
| Sedež ventila | Brass |
| Tesnilo | NBR |
| Min. obratovalni tlak [bar] | 0.1 |
| Vrsta | 3 |
| Max. obratovalni tlak [bar] | 10 |
| DN | 12 |
| B [mm] | 50.0 |
| A [mm] | 54.0 |
| Max. sobna temperatura [°C] | 80 |
| Max. temperatura medija [°C] | 90 |