



(slika je simbolična)

[2/2-el.mag.vent.,NC,vod.krm.,230-240V,50-60Hz,FKM,G1/2,0.1-20bar](#)Kategorija: [Solenoid valve, NC, pilot-operated](#)
Šifra: **102919RIE****Kratek opis**

2/2-way solenoid valve brass, NC, pilot operated, 230-240V, 50-60Hz, 16VA, Medium temp. -10°C to 140°C, FKM, G 1/2, PN 0.1 - 20bar

Economy series available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-10
Min. temperatura medija [°C]	-10
Električni priključek	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Ffunkcija	normally closed (NC)
IP zaščita	IP 65 (with connector socket fitted)
Navoj	G 1/2
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Tesnilo	FPM
Min. obratovalni tlak [bar]	0.1
Vrsta	3
DN	12
Max. obratovalni tlak [bar]	20
B [mm]	50.0
A [mm]	54.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	140