



2/2-el.mag.vent.,NO,vod. krm.,24V DC,NBR,G1,PN0.2-16bar

Kategorija: [Solenoid valve, NO, pilot-operated](#)
Šifra: **102957RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve brass, NO, pilot operated, 24 V DC,
Medium temperature -10 °C to 90 °C, G 1, PN 0.2 - 16 bar
Economy series available in three different versions
- Directly operated
- Combined operation
- Pilot-operated
For all applications with compressed air, neutral gases or
low-viscosity, neutral media.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Min. sobna temperatura [°C] | -10 |
| Min. temperatura medija [°C] | -10 |
| Električni priključek | For connector socket Pg 9/Pg 11 acc. to ISO 4400 |
| Ffunkcija | normally open (NO) |
| IP zaščita | IP 65 (with connector socket fitted) |
| Navoj | G 1 |
| Notranji deli | Stainless steel |
| Ohišje | Brass |
| Sedež ventila | Brass |
| Tesnilo | NBR |
| Min. obratovalni tlak [bar] | 0.2 |
| Vrsta | 6 |
| Max. obratovalni tlak [bar] | 16 |
| DN | 25 |
| A [mm] | 54.0 |
| Max. sobna temperatura [°C] | 80 |
| Max. temperatura medija [°C] | 90 |
| B [mm] | 104.0 |