

Datum: 05.02.2025



(slika je simbolična)

## [2/2-potni el.mag. ventil NC, direk. upr., 24 V DC, G 3/8](#)

Kategorija: [Solenoid valve, NC, 24 V DC, standard type](#)  
Šifra: **116531RIE**

### Kratek opis

2/2-way solenoid valve, Brass, NC, directly operated, 24 V DC, Medium temperature max. 80 °C / 90 °C, G 3/8, PN 0 - 10 bar

Standard series available in two different versions:

- Directly operated
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4.

Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4.

Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

### Tehnične Specifikacije

|                             |                                   |
|-----------------------------|-----------------------------------|
| IP zaščita                  | IP 65                             |
| Navoj                       | G 3/8                             |
| Notranji deli               | Stainless steel                   |
| Ohišje                      | Brass                             |
| Sedež ventila               | Brass                             |
| Standardni navoj            | G thread acc. to DIN EN ISO 228-1 |
| Tesnilo                     | FPM                               |
| Vrsta                       | 1                                 |
| DN                          | 5                                 |
| Max. obratovalni tlak [bar] | 10                                |
| B [mm]                      | 52.0                              |
| A [mm]                      | 85.0                              |
| C [mm]                      | 87.0                              |