

Datum: 02.10.2024



(slika je simbolična)

[2/2-potni el.mag. ventil NC, direk. upr., 24 V DC, G 1/8](#)

Kategorija: [Solenoid valve, NC, 24 V DC, standard type](#)
Šifra: **116528RIE**

Kratek opis

2/2-way solenoid valve, Stainless steel, NC, directly operated, 24 V DC, Medium temp. max. 80 °C/90 °C, G 1/8, PN 0 - 10 bar

Standard series available in two different versions:

- Directly operated
- Pilot-operated

Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4. Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4. Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

Tehnične Specifikacije

IP zaščita	IP 65
Navoj	G 1/8
Notranji deli	Stainless steel
Ohišje	Stainless steel 1.4301
Sedež ventila	Stainless steel 1.4301
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Tesnilo	FPM
Vrsta	1
DN	3
Max. obratovalni tlak [bar]	10
B [mm]	40.0
A [mm]	70.0
C [mm]	70.7