

Datum: 03.11.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

2/2-potni el.mag. ventil, NC, prisil. vod. krm., 24 V DC, 3/8

Kategorija: [Solenoid valve, NC, combined operation](#)
Šifra: **102843RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve brass, NC, force pilot operated, 24 V DC, Rp 3/8, NBR, Medium temp. -20 °C to 85 °C, PN 0 - 3 bar Standard series, proven over many years, available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

| | |
|------------------------------|-------------------------------------|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Električni priključek | ISO 4400; cable socket (Pg 11P) |
| Ffunkcija | normally closed (NC) |
| IP zaščita | IP65 (with connector socket fitted) |
| Navoj | Rp 3/8 |
| Notranji deli | Stainless steel |
| Ohišje | Brass |
| Sedež ventila | Brass |
| Standardni navoj | Rp thread acc. to ISO 7-1 |
| Tesnilo | NBR |
| Max. obratovalni tlak [bar] | 3 |
| Vrsta | 3 |
| DN | 16 |
| Max. sobna temperatura [°C] | 50 |
| B [mm] | 70.0 |
| A [mm] | 80.0 |
| Max. temperatura medija [°C] | 85 |