

Datum: 24.08.2024



2/2-potni el.mag. ventil, NC, vod. krm., 24 V DC, 1

Kategorija: [Solenoid valve, NC, pilot-operated](#)
Šifra: **102874RIE**

(slika je simbolična)

Kratek opis

2/2-way solenoid valve brass, NC, pilot operated, 24 V DC, Medium temperature -20 °C to 120 °C, Rp 1, PN 0.35 - 9 bar Standard series, proven over many years, available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Električni priključek	ISO 4400; cable socket (Pg 11P)
Ffunkcija	normally closed (NC)
IP zaščita	IP65 (with connector socket fitted)
Navoj	Rp 1
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Standardni navoj	Rp thread acc. to ISO 7-1
Tesnilo	FKM
Min. obratovalni tlak [bar]	0.35
Vrsta	4
Max. obratovalni tlak [bar]	9
DN	25
Max. sobna temperatura [°C]	50
A [mm]	80.0
B [mm]	95.0
Max. temperatura medija [°C]	120