

Datum: 27.07.2024

(slika je simbolična)

[2/2-potni el.mag. ventil, NO, prisil. vod. krm., 230 V, 1](#)

Kategorija: [Solenoid valve, NO, combined operation](#)Šifra: **136148RIE**

Kratek opis

2/2-way solenoid valve brass, NO, force pilot operated, 230 V, 50 - 60 Hz, Rp 1, NBR, Medium temp. -20 °C to 85 °C, PN 0 - 9 bar

Standard series, proven over many years, available in three different versions

- Directly operated
- Combined operation
- Pilot-operated

For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Električni priključek	ISO 4400; cable socket (Pg 11P)
Ffunkcija	normally open (NO)
IP zaščita	IP65 (with connector socket fitted)
Navoj	Rp 1
Notranji deli	Stainless steel
Ohišje	Brass
Sedež ventila	Brass
Standardni navoj	Rp thread acc. to ISO 7-1
Tesnilo	NBR
Vrsta	3
Max. obratovalni tlak [bar]	9
DN	25
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	85
A [mm]	86.0
B [mm]	95.0