

Datum: 03.07.2024



(slika je simbolična)

2/2-preklopni vzvodni ventil, obe strani, hitri priklop, G 1/4

Kategorija: [2/2-way toggle valve, discharge port on both sides](#)Šifra: **107016RIE**

Kratek opis

2/2-way toggle lever valve, both sides, Quick connector for hose 10/8, G 1/4, PN max. 8 bar, Temperature -20 °C to 80 °C

Manually operated toggle valve, 2/2-way types. For all applications where compressed air must be switched on or off quickly and easily or a cylinder operated manually. Designed as a banjo-type valve with a hollow bolt and ring piece. Suitable for screwing directly into the equipment or for panel mounting. Compact type of construction, also ideal where space is restricted.

Tehnične Specifikacije

| | |
|--------------------------------|--------------------------------------|
| Min. temperaturno območje [°C] | -20 |
| Navoj | G 1/4 |
| Navoj za pritrditev plošče | M12x0.75 (max. plate thickness 4 mm) |
| Nihajna roka | Nickel-plated brass |
| Notranji deli | Brass with a bare metal surface |
| Povezava | Discharge port on both sides |
| Preklop | Nickel-plated brass |
| Tesnilo | NBR |
| Votli vijak | Nickel-plated brass |
| Vrsta povezave | Quick lock screw fitting |
| Zarobljena tesnila | Polyamide (glass fibre-reinforced) |
| Ffunkcija | 2/2-way |
| Max. obratovalni tlak [bar] | 8 |
| Za cevi [mm] | 10/8 |
| a/f [mm] | 17 |
| C [mm] | 28.5 |
| B [mm] | 60.0 |
| Max. temperaturno območje [°C] | 80 |