

Datum: 03.07.2024



(slika je simbolična)

## 2/2-preklopni vzvodni ventil, obe strani, hitri priklop, G 1/8

Kategorija: [2/2-way toggle valve, discharge port on both sides](#)Šifra: **107010RIE**

### Kratek opis

2/2-way toggle lever valve, both sides, Quick connector for hose 5/3, G 1/8, PN max. 8 bar, Temperature -20 °C to 80 °C  
Manually operated toggle valve, 2/2-way types. For all applications where compressed air must be switched on or off quickly and easily or a cylinder operated manually. Designed as a banjo-type valve with a hollow bolt and ring piece. Suitable for screwing directly into the equipment or for panel mounting. Compact type of construction, also ideal where space is restricted.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Navoj	G 1/8
Navoj za pritrditev plošče	M12x0.75 (max. plate thickness 4 mm)
Nihajna roka	Nickel-plated brass
Notranji deli	Brass with a bare metal surface
Povezava	Discharge port on both sides
Preklop	Nickel-plated brass
Tesnilo	NBR
Votli vijak	Nickel-plated brass
Vrsta povezave	Quick lock screw fitting
Zarobljena tesnila	Polyamide (glass fibre-reinforced)
Ffunkcija	2/2-way
Za cevi [mm]	5/3
Max. obratovalni tlak [bar]	8
a/f [mm]	14
C [mm]	25.0
B [mm]	55.0
Max. temperaturno območje [°C]	80