

Datum: 03.11.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

## **3-pot. krog. ventil, T-izpust, ner.jeklo 1.4408, G 1/4, DN 8**

Kategorija: [553](#)  
Šifra: **135928RIE**

(slika je simbolična)

### **Kratek opis**

3-way ball valve, T-hole, Stainless steel 1.4408, G 1/4, DN 8, Operating temperature -20 °C to 180 °C, PN max. 63 bar With L or T-bore, reduced bore.  
Version for sealing on all sides with integrated ISO flange plate (ISO 5211).  
The lever can be turned 360° to allow several switching variants.

### **Tehnične Specifikacije**

Min. delovna temperatura [°C]	-20
Bore diameter padlock ISO 5211	ca. 7.9 F 04
Krogelno tesnilo	RTFE (15 % glass fibre reinforced PTFE)
Krogla	Stainless steel 1.4401
Navoj	G 1/4
Ohišje	Stainless steel 1.4408
Ročica	Stainless steel 1.4301, with plastic coating
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	RTFE (15 % glass fibre reinforced PTFE)
DN	8
H2 [mm]	9.0
C Ø [mm]	11.0
H1 [mm]	38.2
Delovni tlak	63 bar (dependent on temperature)
L [mm]	75.7
B [mm]	77.5
A [mm]	112.0
Max. delovna temperatura [°C]	180