

Datum: 24.08.2024



(slika je simbolična)

## **3-potni krogelni ventil, nikljana medenina, L-izpust, Rp 3/4**

Kategorija: [3-way ball valve, lower media connection, L-bore](#)  
Šifra: **136329RIE**

### **Kratek opis**

3-way ball valve, nickel-plated brass, Connection bottom, L-hole, Rp 3/4, DN 20, Operating temp. -15 °C to 120 °C, PN max. 16 bar

3-way ball valve with full throughput, integrated ISO flange plate (ISO 5211) and double-sided sealed ball. Pressurisation is only possible via the lower connection.

### **Tehnične Specifikacije**

Min. delovna temperatura [°C]	-15
Krogelno tesnilo	PTFE
Krogla	Nickel-plated brass (CW617N)
Material navojev	Brass
Navoj	Rp 3/4
Ohišje	Nickel-plated brass (CW617N)
Ročica	Steel with plastic coating
Standardni navoj	Rp thread acc. to ISO 7-1
Stebelno tesnilo	PTFE / FKM
PN [bar]	16
E [mm]	16.3
DN	20
a/f [mm]	32
H2 [mm]	39.5
H1 [mm]	42.0
B [mm]	43.0
L [mm]	74.0
A [mm]	115.0
Max. delovna temperatura [°C]	120