

Datum: 03.07.2024



(slika je simbolična)

[3-potni krogelni ventil, nikljana medenina, T-izpust, Rp 3/8](#)

Kategorija: [3-way ball valve, lower media connection, T-bore](#)
Šifra: **136335RIE**

Kratek opis

3-way ball valve, nickel-plated brass, Connection bottom, T-hole, Rp 3/8, DN 10, Operating temp. -15 °C to 120 °C, PN max. 25 bar

3-way ball valve with full throughput, integrated ISO flange plate (ISO 5211) and double-sided sealed ball. Pressurisation is only possible via the lower connection.

Tehnične Specifikacije

| | |
|-------------------------------|------------------------------|
| Min. delovna temperatura [°C] | -15 |
| Krogelno tesnilo | PTFE |
| Krogla | Nickel-plated brass (CW617N) |
| Material navojev | Brass |
| Navoj | Rp 3/8 |
| Ohišje | Nickel-plated brass (CW617N) |
| Ročica | Steel with plastic coating |
| Standardni navoj | Rp thread acc. to ISO 7-1 |
| Stebelno tesnilo | PTFE / FKM |
| DN | 10 |
| E [mm] | 11.4 |
| a/f [mm] | 22 |
| PN [bar] | 25 |
| H2 [mm] | 26.0 |
| H1 [mm] | 28.5 |
| L [mm] | 52.0 |
| B [mm] | 60.0 |
| A [mm] | 115.0 |
| Max. delovna temperatura [°C] | 120 |