

Datum: 02.10.2024



(slika je simbolična)

3/2-5/2-potni ventil NAMUR, G 1/4 (1), G 1/4 (3+5), 230 V, 50 Hz

Kategorija: [3/2 and 5/2-way valves NAMUR](#)
Šifra: **103649RIE**

Kratek opis

3/2-5/2-way valve NAMUR, Alu, Temp. -5 °C to 50 °C, Working pressure 1.5-8 bar, Connection G 1/4 (1), G 1/4 (3 + 5), 230 V, 50 Hz
Pilot-operated 3/2 and 5/2-way spool valves with threaded ports and a NAMUR style interface.
Combines high-quality design with a low price.
By adding the conversion plate supplied with each valve, the device can be adapted to a 3/2-way function.
The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure.
Includes a manual operator as standard.

Tehnične Specifikacije

| | |
|-------------------------------|--|
| Min. delovna temperatura [°C] | -5 |
| Električni priključek | Connector socket PG 9 with LED display |
| Ohišje | Aluminium |
| Port 1 | G 1/4 |
| Port 3 | G 1/4 |
| Port 5 | G 1/4 |
| Ročno upravljanje | latching/non-latching |
| Srednje | Air, neutral gases (filtered) |
| Tesnilo | NBR |
| Min. delovni tlak [bar] | 1.5 |
| DN | 8 |
| Max. delovni tlak [bar] | 8 |
| Max. delovna temperatura [°C] | 50 |
| Napetost | 230 V, 50 Hz |
| Pretok [l/min] | 1370 |