

Datum: 22.07.2024



(slika je simbolična)

## [3/2-5/2-potni ventil, NAMUR, povratna vzmet, G 1/4, 24 V DC](#)

Kategorija: [3/2-5/2-way spool valve, combined spring return](#)  
Šifra: **103656RIE**

### Kratek opis

3/2-5/2-way valve, NAMUR, Spring return, Operating temp. -20 °C to 50 °C, Working pressure 2.5 - 10 bar, Connection G 1/4, 24 V DC  
Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Električni priključek	Connector socket Pg 9 Plug connector PG 9, conversion plate, screws and seal
Obseg dobave	Aluminium anodised G 1/4 (Port 1), G 1/4 (Port 3 and 5)
Ohišje	latching
Povezava	Air, neutral gases (filtered)
Ročno upravljanje	NBR
Srednje	Stainless steel
Tesnilo	2.5
Tuljava	3 W=/ 5 VA~
Min. delovni tlak [bar]	7
Vhodna moč	10
DN	24 V DC
Max. delovni tlak [bar]	50
Napetost	1250
Max. delovna temperatura [°C]	
Pretok [l/min]	