

Datum: 03.07.2024



3/2-potni mag. ventil lineonline s kontroliranim izpustom NC 8

Kategorija: [Metalwork](#)
Šifra: **106848RIE**

(slika je simbolična)

Kratek opis

3/2-way solenoid valve »lineonline«, Controlled venting, Hose - hose, for hose Ø 8, NC, 24 V DC, Operating pre. 2.5-7 bar

Though small in size, these valves are solenoid-piloted and feature very high performance.

Each valve comes complete with a monostable manual control and LED. Exhaust can be damped with a silencer or conveyed via a pipe fitting.

Function corresponds to the normal position of the valve.

Tehnične Specifikacije

| | |
|--|--|
| Min. temperaturno območje [°C] | -20 |
| Ffunkcija | NC |
| Notranji deli | Nickel-plated brass, brass, technopolymer, stainless steel |
| Pnevmatski simboli | On housing |
| Telo | Technopolymer |
| Tesnilo | NBR |
| Vhodna moč | 1.2 W |
| Min. obratovalni tlak [bar] | 2.5 |
| Max. obratovalni tlak [bar] | 7 |
| Za cevi Ø [mm] | 8 |
| l [mm] | 18.7 |
| Operativna napetost | 24 V DC |
| A [mm] | 57.2 |
| Max. temperaturno območje [°C] | 60 |
| B [mm] | 63.5 |
| Pretok pri 6,3 bar in Δp 1,0 bar [l/min] | 700 |