

Datum: 02.10.2024



(slika je simbolična)

3/2-potni magnetni ventil z dušilko, G 1/4, NC, za cev 6

Kategorija: [Metalwork](#)Šifra: **106853RIE**

Kratek opis

3/2-way solenoid valve »lineonline« silenced venting, Hose - thread, G 1/4, Hose Ø 6, NC, 24 V DC, Operating pressure 2.5 - 7 bar

Though small in size, these valves are solenoid-piloted and feature very high performance.

Each valve comes complete with a monostable manual control and LED. Exhaust can be damped with a silencer or conveyed via a pipe fitting.

Function corresponds to the normal position of the valve.

Tehnične Specifikacije

| | |
|---|--|
| Min. temperaturno območje [°C] | -20 |
| Ffunkcija | NC |
| Navoj | G 1/4 |
| Notranji deli | Nickel-plated brass, brass, technopolymer, stainless steel |
| Pnevmatski simboli | On housing |
| Telo | Technopolymer |
| Tesnilo | NBR |
| Vhodna moč | 1.2 W |
| Min. obratovalni tlak [bar] | 2.5 |
| Za cevi Ø [mm] | 6 |
| Max. obratovalni tlak [bar] | 7 |
| l [mm] | 14.6 |
| Operativna napetost | 24 V DC |
| B [mm] | 57.5 |
| Max. temperaturno območje [°C] | 60 |
| A [mm] | 61.3 |
| Pretok pri 6,3 bar in Δp 1,0 bar [Nl/min] | 380 |