



3/2-potni mini el.magnet. ventil neposred. upravl., NO, 12 VDC

Kategorija: [Miniature solenoid valves](#)
Šifra: **106649RIE**

(slika je simbolična)

Kratek opis

3/2-way mini solenoid valve directly controlled, DN 1.5 mm, NO, 12 VDC, for equipment plug, Pressure 0-5 bar, Temp. -5 °C to 45 °C

Directly controlled 3/2-way solenoid valves specially designed for pneumatic applications. These valves are provided with a flange for assembly on an individual base or multiple manifold base. They feature a monostable manual operator. The scope of supply includes two fixing bolts and a flange gasket. The coils can be turned 180°.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-5
Material	Plastic
Ploščica na ročnem upravljalcu	Black
Povezava	For plug connector
Srednje	Filtered, unlubricated compressed air
Tesnilo	NBR, stainless steel
Nominalni Ø [mm]	1.5
Moč tuljave [W]	2.5
Ffunkcija	3/2 NO
Max. obratovalni tlak [bar]	5
Odpiranje in zapiranje krat	10 to 12 ms (depending on pressure)
Napetost	12 V DC
Premer [mm]	15.0
Višina [mm]	42.0
Max. temperaturno območje [°C]	45