

Datum: 03.07.2024



(slika je simbolična)

3/2-preklopni vzvodni ventil, smer cevi, pot.i prik., G 1/4

Kategorija: [3/2-way toggle valve, pressure port on hose side](#)
Šifra: **107035RIE**

Kratek opis

3/2-way toggle lever valve, Hose side, Push-in connector hose 8, G 1/4, PN max. 8 bar, Temp. -20 °C to 80 °C, nickel-plated brass
Manually operated toggle valve, 3/2-way types. For all applications where compressed air must be switched on or off quickly and easily or a cylinder operated manually. Designed as a banjo-type valve with a hollow bolt and ring piece. Suitable for screwing directly into the equipment or for panel mounting. Compact type of construction, also ideal where space is restricted.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Navoj	G 1/4
Navoj za pritrditev plošče	M12x0.75 (max. plate thickness 4 mm)
Nihajna roka	Nickel-plated brass
Notranji deli	Brass with a bare metal surface
Povezava	Pressure port on hose side
Preklop	Nickel-plated brass
Tesnilo	NBR
Votli vijak	Nickel-plated brass
Vrsta povezave	Plug-in connector
Zarobljena tesnila	Polyamide (glass fibre-reinforced)
Ffunkcija	3/2-way
Max. obratovalni tlak [bar]	8
Za cevi [mm]	8
a/f [mm]	17
C [mm]	24.0
B [mm]	60.0
Max. temperaturno območje [°C]	80