

Datum: 03.11.2024



[3/2 ventil »FUTURA«, Elektr. voden, 230 V AC, Velikost 4, G 3/4](#)

Kategorija: [3/2-way valve, electrically operated, 230 V AC](#)Šifra: **100304RIE**

(slika je simbolična)

Kratek opis

3/2-way valve »FUTURA«, electr. actuated with solenoid 230 V AC, 50 Hz, Size 4, G 3/4, Exhaust G 1/2, Input pressure 2 - 10 bar

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal.

3/2-way type including silencer.

When they are switched off, the system is exhausted at the same time.

Tehnične Specifikacije

| | |
|--|--|
| Min. temperaturno območje [°C] | -10 |
| Električni priključek | Socket coupling EN 175301-803, form C, poles 2+PE |
| IP zaščita | IP 65 |
| Izpušni zrak | G 1/2 At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Merjenje pretoka | G 3/4 |
| Navoj | PA66 GF60 |
| Ohišje | Material: Die-cast zinc |
| Priključni navoj | FUTURA |
| Serijska | Compressed air, neutral gases |
| Srednje | |
| Zaklepna moč pri 50 Hz AC napetosti [VA] | 1.6 |
| Min. vhodni tlak [bar] | 2 |
| Dvižna moč pri 50 Hz AC napetosti [VA] | 2.2 |
| Vhodna moč | 2.5 Watt with DC voltage |
| Velikost | 4 |
| Max. vhodni tlak [bar] | 10 |
| Max. temperaturno območje [°C] | 50 |
| A [mm] | 85.0 |
| Delovni cikel [%] | 100 |
| C [mm] | 110.7 |
| B [mm] | 177.7 |
| Pretok [l/min] | 12500 |