

Datum: 02.10.2024



3/2 ventil »FUTURA«, pnevmatsko voden, Velikost 4, G 1

Kategorija: [3/2-way valves, pneumatically operated](#)
Šifra: **156619RIE**

(slika je simbolična)

Kratek opis

3/2-way valve »FUTURA«, pneumatically actuated, Size 4, G 1, Exhaust G 1/2, Input pressure max. 16 bar, Temp. -10 °C to 50 °C

Pneumatic systems or parts of systems can be switched on and off by means of an pneumatic signal.
3/2-way type including silencer.

When they are switched off, the system is exhausted at the same time.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Izpušni zrak	G 1/2 At P ₂ = 6 bar and pressure drop Δ _p = 1 bar
Merjenje pretoka	G 1 PA66 GF60
Navoj	Material: Die-cast zinc FUTURA
Ohišje	Compressed air, neutral gases
Priključni navoj	4
Serijska	Max. vhodni tlak [bar] 16
Srednje	Max. temperaturno območje [°C] 50
Velikost	C [mm] 78.0
Max. vhodni tlak [bar]	A [mm] 85.0
Max. temperaturno območje [°C]	B [mm] 145.0
C [mm]	Pretok [l/min] 12500
A [mm]	
B [mm]	
Pretok [l/min]	