

Datum: 26.12.2024



(slika je simbolična)

## [3/2-way toggle lever valve, Hose side, screw connection, G 1/4](#)

Kategorija: [3/2toggle v.,pressure port hose side, screw conn.](#)  
Šifra: **107027RIE**

### Kratek opis

3/2-way toggle lever valve, Hose side, screw connection hose G1/4 IT, G 1/4, PN max.8bar, Temp. -20°C to 80°C, nickel-plated brass  
Manually operated toggle valve, 3/2-way types. For all applications where compressed air must be switched on or off quickly and easily or a cylinder operated manually. Designed as a banjo-type valve with a hollow bolt and ring piece. Suitable for screwing directly into the equipment or for panel mounting. Compact type of construction, also ideal where space is restricted.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Navoj	G 1/4
Navoj za pritrditev plošče	M12x0.75 (max. plate thickness 4 mm)
Nihajna roka	Nickel-plated brass
Notranji deli	Brass with a bare metal surface
Povezava	Pressure port on hose side
Preklop	Nickel-plated brass
Tesnilo	NBR
Votli vijak	Nickel-plated brass
Vrsta povezave	Screw connection
Za cevi [mm]	G 1/4 female thread
Zarobljena tesnila	Polyamide (glass fibre-reinforced)
Ffunkcija	3/2-way
Max. obratovalni tlak [bar]	8
a/f [mm]	17
C [mm]	22.0
B [mm]	60.0
Max. temperaturno območje [°C]	80