

Datum: 24.08.2024



(slika je simbolična)

Batni kotni ventil, NC, bronasti, G 1 1/2

Kategorija: [Angle-seat valves, piston actuator bronze version](#)
Šifra: **133203RIE**

Kratek opis

Angle seat valve, Piston drive without NAMUR interface, Bronze, Medium temp. -10°C to 180°C, G 1 1/2, Pressure differ. max 11 bar

Angle-seat valves with external pilot control and a self-aligning valve disc for neutral (bronze body) or corrosive (stainless steel body) media.

- Very high flow due to angled seat design
- Water hammer prevented by fluid entry under the disc
- Suitable for vacuum operation (low vacuum)

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-10
Bat	PBT + GF 30 %
Ffunkcija	NC
Nadzor zraka	G 1/8
Navoj	G 1 1/2
Ohišje	Bronze
Operater	Polyamide (glass fibre-reinforced)
Priključki	Stainless steel
Steblo	Stainless steel
Tesnilo	PTFE
Min. vodeni tlak [bar]	4
Max. vodeni tlak [bar]	8
Max. razlika v delovnem tlaku [bar]	11
Diferencialni tlak max. [bar]	16
Max. dovoljeni statični tlak [bar]	16
Max. temperatura vodenega medija [°C]	60
Max. sobna temperatura [°C]	70
F [mm]	120.0
Max. temperatura medija [°C]	180
C [mm]	264.0
A [mm]	270.0