



## Cilinder s kratkim hodom del. v dveh smereh bat Ø 80hod 25G 3/8

Kategorija: [Short-stroke cylinder, double-acting, with magnet](#)  
Šifra: **115155RIE**

(slika je simbolična)

### Kratek opis

Short stroke cylinder »ACQ« double-acting, Magnet, Piston Ø 80, Stroke 25, G 3/8, Working pressure 1-10 bar, Temp. -20°C to 70°C  
Suitable for installation in limited spaces.  
Supplied with magnet.  
Short-stroke cylinders in two different versions:  
»ACQ« Series, double-acting, Ø 12 to 100  
»ASQ« Series, single-acting, Ø 12 to 63  
Suitable for filtered, unlubricated or lubricated compressed air.  
If lubrication is used, it must be continuous.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Steel, thick-chromed
Batnica IT	M16x2.0
Cushioning	non-cushioned
Ffunkcija	double-acting
Gewinde Kolbenstange	female piston rod
Magnet	with magnet
Ovoj	Aluminium
Povezava	G 3/8
Serija	ACQ series
Tesnilo	NBR
Min. delovni tlak [bar]	1
Vrsta	3
Max. delovni tlak [bar]	10
Batnica Ø [mm]	25
Stroke [mm]	25
Max. temperaturno območje [°C]	70
Bat Ø [mm]	80