



(slika je simbolična)

Coaxial valve pneumat. actuated, single-acting NC, FKM, Rp 1/2

Kategorija: [Coaxial valve, single-acting - spring to close,FKM](#)
Šifra: **103736RIE**

Kratek opis

Coaxial valve pneumat. actuated, single-acting, NC, nickel-plated brass, Temp. -20°C to 150°C, Control pressure 4.2-8 bar, Rp 1/2

2/2-way coaxial valves, specially designed for automated industrial plant engineering.

A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator.

These valves have a full bore and - owing to the optimised design - only minimal flow losses.

They are controlled by means of filtered compressed air.

Tehnične Specifikacije

| | |
|-------------------------------|------------------------------------|
| Min. delovna temperatura [°C] | -20 |
| Navoj | Rp 1/2 |
| Notranji deli | Nickel-plated brass |
| Ohišje | Nickel-plated brass |
| Povezava | NAMUR interface, direct: 2 x G 1/8 |
| Različica | single-acting - spring to close |
| Tesnilo | FKM |
| Vgradni položaj | Any |
| Vzmet | Stainless steel |
| Min. vodeni tlak [bar] | 4.2 |
| Max. vodeni tlak [bar] | 8 |
| Max. obratovalni tlak [bar] | 10 |
| DN | 15 |
| H [mm] | 51.7 |
| L [mm] | 112.0 |
| Max. delovna temperatura [°C] | 150 |