

Datum: 02.10.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

## Diferencialni manometer, vzporedni, 2 x G 1/2, 0-1 bar, Ø 100

Kategorija: [Wika](#)  
Šifra: **102578RIE**

(slika je simbolična)

### Kratek opis

Differential pressure gauge, 2 parallel radial male end connections below, G 1/2, Goods class 1.6, Measurement range 0-1 bar, Ø100  
Bourdon-tube pressure gauge with parallel male connector and two separate measuring systems.  
For measuring differential pressures or two different pressures.  
Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material Prozessanschluss	Copper alloy
Merilni element	Copper alloy
Ohišje	Steel, black
Okvir	steel, black
Položaj povezave	radial on bottom
Povezava	G 1/2
Prednje steklo	Flat instrument glass
Premikanje	Copper alloy
Spodnja/Zgornja meja območja	Positive pressure
Stopnja rasti na območju skale - bar [bar]	0.02
Merilno območje max. bar	1
Razred točnosti	1.6
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Premer [mm]	100
Vrsta	111.10