



Diferencialni manometer, vzporedni, 2 x G 1/2, 0-4 bar, Ø 100

Kategorija: [Wika](#)
Šifra: **102581RIE**

(slika je simbolična)

Kratek opis

Differential pressure gauge, 2 parallel radial male end connections below, G 1/2, Goods class 1.6, Measurement range 0-4 bar, Ø100
Bourdon-tube pressure gauge with parallel male connector and two separate measuring systems.
For measuring differential pressures or two different pressures.
Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

| | |
|--|-----------------------|
| Min. sobna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Material Prozessanschluss | Copper alloy |
| Merilni element | Copper alloy |
| Ohišje | Steel, black |
| Okvir | steel, black |
| Položaj povezave | radial on bottom |
| Povezava | G 1/2 |
| Prednje steklo | Flat instrument glass |
| Premikanje | Copper alloy |
| Spodnja/Zgornja meja območja | Positive pressure |
| Stopnja rasti na območju skale - bar [bar] | 0.1 |
| Razred točnosti | 1.6 |
| Merilno območje max. bar | 4 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| Premer [mm] | 100 |
| Vrsta | 111.10 |