

Datum: 03.07.2024



(slika je simbolična)

Elektr. Tlačni pretvornik, 0 - 4 bar, G 1/2, CrNi jeklo1.4571

Kategorija: [Wika](#)
Šifra: **102729RIE**

Kratek opis

Electr. pressure transducer, general industrial applications, Non-linearity 0.25%, Meas. range 0 - 4 bar, G 1/2, CrNi steel 1.4571

Pressure transmitters, very high precision, in CrNi steel, for complex measurement tasks in the process industry as well as research and development.

Applications: Low temperature or outdoor applications, extreme shock loads and vibration levels, corrosive media in the chemical industry.

Compatible with all internationally established process connections.

Tehnične Specifikacije

| | |
|------------------------------|---|
| Min. sobna temperatura [°C] | -30 |
| Min. temperatura medija [°C] | -30 |
| Deli v kontaktu z medijem | CrNi-steel 1.4571 With right-angle connector acc. to DIN EN 175301-803 A |
| Električni priključek | IP 65 acc. to EN 60529 |
| IP zaščita | G 1/2 |
| Navoj | up to 0.25% of span |
| Nelinearnost | CrNi-steel 1.4571 |
| Ohišje | DC 8 ... 36 V |
| Operativna napetost | Positive pressure |
| Spodnja/Zgornja meja območja | S-20 |
| Vrsta | 4 - 20 mA, 2-wire |
| izhodni signal | 4 |
| Merilno območje max. bar | 100 |
| Max. sobna temperatura [°C] | 100 |
| Max. temperatura medija [°C] | 100 |