



(slika je simbolična)

Filter»FUTURA«Kov. pos.5µm, Vel. 2, G3/8, Pol avto.

Kategorija: [Filter with metal bowl and sight glass](#)Šifra: **139506RIE**

Kratek opis

Filter »FUTURA« with metal container and viewing tube, 5 µm, Size 2, G 3/8, 1.5 - 16 bar, Temp. -10 °C to 50 °C, Semi-automatic
Filters with excellent flow rates in modern design.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -10 |
| Element filtra | Cellpor (PE) |
| Merjenje pretoka | At P ₂ = 6 bar and pressure drop Δ _p = 1 bar |
| Navoj | G 3/8 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | PA66 GF60 |
| Posoda | Metal container with viewing tube |
| Priključni navoj | Material: Die-cast zinc |
| Serijska | FUTURA |
| Srednje | Compressed air, neutral gases |
| Tesnilo | NBR |
| Min. vhodni tlak [bar] | 1.5 |
| Velikost | 2 |
| Rang filtra [µm] | 5 |
| Max. vhodni tlak [bar] | 16 |
| C [mm] | 42.5 |
| Max. temperaturno območje [°C] | 50 |
| A [mm] | 63.0 |
| B [mm] | 193.5 |
| Pretok [l/min] | 3500 |