



(slika je simbolična)

## Filter»FUTURA«PC zbir.5 µmVel.4,G 3/4Pol avt.

Kategorija: [Filter with polycarbonate bowl and bowl guard](#)Šifra: **100149RIE**

### Kratek opis

Filter »FUTURA« with PC container and protective cage, 5 µm, Size 4, G 3/4, 1.5 - 16 bar, Temp. -10 °C to 50 °C, Semi-automatic  
Filters with excellent flow rates in modern design.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Merjenje pretoka	At P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 1 bar
Navoj	G 3/4
Odtok kondenzata	Semi-automatic
Ohišje	PA66 GF60
Posoda	Polycarbonate container with protective cage
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Min. vhodni tlak [bar]	1.5
Velikost	4
Rang filtra [µm]	5
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
C [mm]	58.0
A [mm]	85.0
B [mm]	247.0
Pretok [l/min]	8000