

Datum: 24.08.2024



(slika je simbolična)

Filter»G«,Kov. pos.,Kazalno okence,5 µmVel. 600G 1

Kategorija: [Filter with metal bowl, sight glass](#)Šifra: **116413RIE**

Kratek opis

Filter »G« metal container, Viewing tube, Mounting bracket,
5 µm, Size 600, G 1, Input pres. max 10 bar, Working pres.
1.5-9 bar
Centrifugal separators with a sintered filter element.

Tehnične Specifikacije

| | |
|---------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj | G 1 |
| Odtok kondenzata | Semi-automatic |
| Ohišje | Die-cast aluminium |
| Posoda | Metal container with viewing tube |
| Serija | G |
| Tesnilo | NBR |
| Min. delovni tlak [bar] | 1.5 |
| Rang filtra [µm] | 5 |
| Max. delovni tlak [bar] | 9 |
| Max. vhodni tlak [bar] | 10 |
| C [mm] | 37.0 |
| Max. sobna temperatura [°C] | 70 |
| Max. temperatura medija [°C] | 70 |
| A [mm] | 85.0 |
| D [mm] | 219.0 |
| B [mm] | 256.0 |
| Velikost | 600 |
| Pretok [l/min] | 7800 |