



Filter»G«,PC zbir.,Zaščitna kletka,5 µmVel. 300G 3/8

Kategorija: [Filter with polycarbonate bowl, bowl guard](#)
Šifra: **116397RIE**

(slika je simbolična)

Kratek opis

Filter »G« PC container, Protective cage, Mounting bracket,
5 µm, Size 300, G 3/8, Input pres. max 10 bar, Working pres.
1.5-9 bar
Centrifugal separators with a sintered filter element.

Tehnične Specifikacije

| | |
|---------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/8 |
| Odtok kondenzata | Fully-automatic |
| Ohišje | Die-cast aluminium |
| Posoda | Polycarbonate container with protective cage |
| Serija | G |
| Tesnilo | NBR |
| Min. delovni tlak [bar] | 1.5 |
| Rang filtra [µm] | 5 |
| Max. delovni tlak [bar] | 9 |
| Max. vhodni tlak [bar] | 10 |
| C [mm] | 21.0 |
| A [mm] | 51.0 |
| Max. sobna temperatura [°C] | 70 |
| Max. temperatura medija [°C] | 70 |
| D [mm] | 143.0 |
| B [mm] | 164.0 |
| Velikost | 300 |
| Pretok [l/min] | 1800 |