



## Filter »GA« PC zbir.Zašč. kletka, 5µm, Vel. 400, G1/2

Kategorija: [Filter with polycarbonate bowl, bowl guard](#)  
Šifra: **178465RIE**

(slika je simbolična)

### Kratek opis

Filter »GA« PC container, Protective cage, Mounting bracket, 5 µm, Size 400, G1/2, Input pres. max 10 bar, Working pres. 1.5-9 bar  
Centrifugal separators with a sintered filter element.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-5
Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Fully-automatic
Ohišje	Die-cast aluminium
Posoda	Polycarbonate container with protective cage
Serijska	GA
Tesnilo	NBR
Min. delovni tlak [bar]	1.5
Rang filtra [µm]	5
Max. delovni tlak [bar]	9
Max. vhodni tlak [bar]	10
C [mm]	42.5
Max. temperaturno območje [°C]	70
A [mm]	80.0
D [mm]	177.5
B [mm]	220.0
Velikost	400
Pretok [l/min]	4600