

Datum: 24.08.2024



(slika je simbolična)

## Filter reg.»FUTURA« Kov. Vel.4, G 3/4, 0.1-2 bar Pol avto.

Kategorija: [Filter regulator with metal bowl and sight glass](#)Šifra: **151827RIE**

### Kratek opis

Filter regulator »FUTURA«, with metal container, Viewing tube, Pressure gauge, 5 µm, Size 4, G 3/4, Control range 0.1-2 bar, Semi  
Filter regulators with excellent flow rates in modern design. The regulator knob can be latched and locked.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
Merjenje pretoka	At P <sub>1</sub> = 10 bar, P <sub>2</sub> = 6.3 bar and pressure drop Δ <sub>p</sub> = 1 bar
Navoj	G 3/4
Odtok kondenzata	Semi-automatic
Ohišje	PA66 GF60
Poraba zraka	Yes
Posoda	Metal container with viewing tube
Priključni navoj	Material: Die-cast zinc
Serija	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Min. krmilno območje [bar]	0.1
Max. notranja poraba zraka	1.5 l/min (depending on secondary pressure)
Min. vhodni tlak [bar]	1.5
Max. krmilno območje [bar]	2
Zaslon manometra max. [bar]	2.5
Velikost	4
Rang filtra [µm]	5
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
A [mm]	85.0
C [mm]	137.0
B [mm]	326.0
Pretok [l/min]	13000