



## Filter reg.»FUTURA« PC, Vel.2, G 1/2, 0.2-4 bar, Avt.

Kategorija: [Filter regulator, polycarbonate bowl, bowl guard](#)  
Šifra: **151801RIE**

(slika je simbolična)

### Kratek opis

Filter regulator »FUTURA«, with PC container, Protective cage, Pressure gauge, 5 µm, Size 2, G 1/2, Control range 0.2-4 bar, Fully  
Filter regulators with excellent flow rates in modern design. The regulator knob can be latched and locked.

### Tehnične Specifikacije

|                                |   |
|--------------------------------|---|
| Min. temperaturno območje [°C] | -10   |
| Element filtra                 | Cellpor (PE)  |
| Membrane                       | NBR   |
| Merjenje pretoka               | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                          | G 1/2   |
| Odtok kondenzata               | Fully-automatic   |
| Ohišje                         | PA66 GF60   |
| Posoda                         | Polycarbonate container with protective cage                            |
| Priključni navoj               | Material: Die-cast zinc   |
| Serijska                       | FUTURA  |
| Srednje                        | Compressed air, neutral gases   |
| Tesnilo                        | NBR   |
| Min. krmilno območje [bar]     | 0.2   |
| Min. vhodni tlak [bar]         | 1.5   |
| Velikost                       | 2   |
| Max. krmilno območje [bar]     | 4   |
| Rang filtra [µm]               | 5   |
| Zaslon manometra max. [bar]    | 6   |
| Max. vhodni tlak [bar]         | 16  |
| Max. temperaturno območje [°C] | 50  |
| A [mm]                         | 63.0  |
| C [mm]                         | 110.0   |
| B [mm]                         | 273.0   |
| Pretok [l/min]                 | 5200  |