

Datum: 24.08.2024



(slika je simbolična)

## Filter reg.»FUTURA« PC, Vel.2, G 3/8, 0.5-16 bar, Pol avto.

Kategorija: [Filter regulator, polycarbonate bowl, bowl guard](#)  
Šifra: **139500RIE**

### Kratek opis

Filter regulator »FUTURA«, with PC container, Protective cage, Pressure gauge, 5 µm, Size 2, G 3/8, Control range 0.5-16 bar, Semi  
Filter regulators with excellent flow rates in modern design.  
The regulator knob can be latched and locked.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra Membrane	Cellpor (PE) NBR
Merjenje pretoka	At P <sub>1</sub> = 10 bar, P <sub>2</sub> = 6.3 bar and pressure drop Δ <sub>p</sub> = 1 bar
Navoj	G 3/8
Odtok kondenzata	Semi-automatic
Ohišje	PA66 GF60
Posoda	Polycarbonate container with protective cage
Priključni navoj	Material: Die-cast zinc
Serijska	FUTURA
Srednje	Compressed air, neutral gases
Tesnilo	NBR
Min. krmilno območje [bar]	0.5
Min. vhodni tlak [bar]	1.5
Velikost	2
Rang filtra [µm]	5
Max. krmilno območje [bar]	16
Max. vhodni tlak [bar]	16
Zaslona manometra max. [bar]	25
Max. temperaturno območje [°C]	50
A [mm]	63.0
C [mm]	110.0
B [mm]	257.0
Pretok [l/min]	4500