

Datum: 24.08.2024



(slika je simbolična)

## Filter reg. »multifix«5 µmVel. 3G 3/4, 0.5 - 10 bar

Kategorija: [Filter regulator with polycarbonate bowl](#)Šifra: **100482RIE**

### Kratek opis

Filter regulator »multifix«, PC container, press. gauge, 5 µm, Size 3, G 3/4, Input pressure max. 16 bar, Control range 0.5-10 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.

The pressure setting can be locked by pushing the button down.

### Tehnične Specifikacije

|                              |   |
|------------------------------|---|
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 3/4   |
| Odtok kondenzata             | Semi-automatic  |
| Ohišje                       | Die-cast zinc   |
| Posoda                       | Polycarbonate container   |
| Serija                       | multifix  |
| Tesnilo                      | NBR   |
| Vzmet pokrova motorja        | POM-brass   |
| Min. krmilno območje [bar]   | 0.5   |
| Velikost                     | 3   |
| Rang filtra [µm]             | 5   |
| Max. krmilno območje [bar]   | 10  |
| Max. vhodni tlak [bar]       | 16  |
| Zaslon manometra max. [bar]  | 16  |
| DN                           | 20  |
| Max. sobna temperatura [°C]  | 60  |
| Max. temperatura medija [°C] | 60  |
| A [mm]                       | 68.8  |
| C [mm]                       | 99.0  |
| D [mm]                       | 147.3   |
| B [mm]                       | 246.3   |
| Pretok [l/min]               | 6700  |