



(slika je simbolična)

## Filter reg. »Stinard«Kov. pos.5 µmVel. 3G 1/2

Kategorija: [Filter regulator with metal bowl](#)  
Šifra: **100937RIE**

### Kratek opis

Filter regulator »Standard«, Metal container and pressure gauge, 5 µm, Size 3, G 1/2, Input pressure max. 25 bar, 0.5 - 16 bar  
Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

### Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Manuel
Ohišje	Die-cast zinc, painted silver
Posoda	Metal container
Serija	Standard
Tesnilo	NBR
Min. krmilno območje [bar]	0.5
Velikost	3
Rang filtra [µm]	5
DN	14
Max. krmilno območje [bar]	16
Max. vhodni tlak [bar]	25
Zaslon manometra max. [bar]	25
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	82.0
F [mm]	83.0
C [mm]	130.0
D [mm]	172.0
Pretok [l/min]	3000