

Datum: 24.08.2024



(slika je simbolična)

Filter reg. »Stinard« Zašč. kletka, 40 µm, Vel.4, G 3/4

Kategorija: [Filter regulator with PC bowl and bowl guard](#)
Šifra: **174094RIE**

Kratek opis

Filter regulator »Standard«, PC container, Protective cage, 40 µm, Size 4, G 3/4, PE max. 16 bar, 0.5 - 10 bar, pilot controlled
Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/4
Odtok kondenzata	Semi-automatic
Ohišje	Aluminium, painted silver
Posoda	Polycarbonate container with protective cage
Serija	Standard
Tesnilo	NBR
Min. krmilno območje [bar]	0.5
Velikost	4
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	16
DN	25
Rang filtra [µm]	40
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	125.0
C [mm]	129.0
D [mm]	263.0
Pretok [l/min]	12000