

Datum: 24.08.2024



(slika je simbolična)

## Filter reg. »Stinard« Zašč. kletka 40 µm Vel. 2, G 3/8

Kategorija: [Filter regulator with PC bowl and bowl guard](#)Šifra: **100930RIE**

### Kratek opis

Filter regulator »Standard«, PC container, Protective cage, 40 µm, Size 2, G 3/8, Input pressure max. 16 bar, 0.5 - 10 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

### Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc, painted silver
Posoda	Polycarbonate container with protective cage
Serija	Standard
Tesnilo	NBR
Min. krmilno območje [bar]	0.5
Velikost	2
Max. krmilno območje [bar]	10
DN	11
Max. vhodni tlak [bar]	16
Zaslona manometra max. [bar]	16
Rang filtra [µm]	40
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	70.0
F [mm]	76.5
C [mm]	120.5
D [mm]	145.9
Pretok [l/min]	1500