

Datum: 01.09.2024



(slika je simbolična)

## Filter regulator »G«, Kovinska posoda, 5 µm, Velikost 600, G 1

Kategorija: [Filter regulator with metal bowl, sight glass](#)  
Šifra: **116368RIE**

### Kratek opis

Filter regulator »G«, with metal container, Viewing tube, Mounting bracket, 5 µm, Size 600, G 1, Input pressure max. 10 bar  
Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.  
The pressure setting can be locked by pushing the button down.

### Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast aluminium
Posoda	Metal container with viewing tube
Serija	G
Tesnilo	NBR
Vzmet pokrova motorja	POM
Min. krmilno območje [bar]	1.5
Rang filtra [µm]	5
Max. krmilno območje [bar]	9
Max. vhodni tlak [bar]	10
Max. sobna temperatura [°C]	70
Max. temperatura medija [°C]	70
A [mm]	85.0
C [mm]	144.0
D [mm]	219.0
B [mm]	363.0
Velikost	600
Pretok [l/min]	7000