

Datum: 24.08.2024



Filter regulator »GA«, PC zbiralnik, 5 µm, Velikost 400, G 3/8

Kategorija: [Filter regulator with PC bowl, bowl guard](#)Šifra: **178478RIE**

(slika je simbolična)

Kratek opis

Filter regulator »GA«, with PC container, Protective cage, Mounting bracket, 5 µm, Size 400, G 3/8, Input pressure max. 10 bar
Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator. The pressure setting can be locked by pushing the button down.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -5 |
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/8 |
| Odtok kondenzata | Fully-automatic |
| Ohišje | Die-cast aluminium |
| Posoda | Polycarbonate container with protective cage |
| Serijska | GA |
| Tesnilo | NBR |
| Vzmet pokrova motorja | POM |
| Min. krmilno območje [bar] | 1.5 |
| Rang filtra [µm] | 5 |
| Max. krmilno območje [bar] | 9 |
| Max. vhodni tlak [bar] | 10 |
| Max. temperaturno območje [°C] | 70 |
| A [mm] | 80.0 |
| C [mm] | 108.0 |
| D [mm] | 177.5 |
| B [mm] | 285.5 |
| Velikost | 400 |
| Pretok [l/min] | 4000 |