

Datum: 03.11.2024

(slika je simbolična)

Filter regulator »multifix«, 40 µm, Velikost 5, G 1, 0.1 - 3 bar

Kategorija: [Filter regulator with polycarbonate bowl](#)
Šifra: **100484RIE**

Kratek opis

Filter regulator »multifix«, PC container, press. gauge, 40 µm, Size 5, G 1, Input pressure max. 16 bar, Control range 0.1 - 3 bar
Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.
The pressure setting can be locked by pushing the button down.

Tehnične Specifikacije

Max. notranja poraba zraka	0,5 l/min (depending on secondary pressure) At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta p = 1$ bar
Merjenje pretoka	G 1
Navoj	Semi-automatic
Odtok kondenzata	Aluminium
Ohišje	Yes
Poraba zraka	Polycarbonate container
Posoda	multifix
Serija	NBR
Tesnilo	POM-brass
Vzmet pokrova motorja	
Min. krmilno območje [bar]	0.1
Max. krmilno območje [bar]	3
Zaslon manometra max. [bar]	4
Velikost	5
Max. vhodni tlak [bar]	16
DN	25
Rang filtra [µm]	40
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	100.0
C [mm]	128.0
D [mm]	253.8
B [mm]	381.8
Pretok [l/min]	15000