



(slika je simbolična)

Filter regulator »Stinard-mali« z PC zbiralnik, 5 µm, G 1/4

Kategorija: [Filter regulator with polycarbonate bowl](#)
Šifra: **100782RIE**

Kratek opis

Filter regulator »Standard-mini« with PC container incl. pressure gauge and control cabinet nut, 5 µm, Size 0, G 1/4, 0.5 - 10 bar
Compact, reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator. The pressure setting can be locked by pushing the knob down.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/4
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc, painted silver
Posoda	Polycarbonate container
Serija	Standard-mini
Tesnilo	NBR
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.5
DN	5
Rang filtra [µm]	5
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslona manometra max. [bar]	16
A [mm]	40.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	65.0
D [mm]	102.0
B [mm]	167.0
Pretok [l/min]	350