

Datum: 03.07.2024



[Filter regulator »variobloc« s kovinsko posodo, Velikost 2, G 1/2](#)

Kategorija: [Filter regulator, metal bowl, incl. sight glass](#)Šifra: **125312RIE**

(slika je simbolična)

Kratek opis

Filter regulator »variobloc«, Metal container incl. viewing tube and pressure gauge, Size 2, G 1/2, Input pressure max. 20 bar

Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator.

The pressure setting can be locked by pushing the knob down.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

| | |
|------------------------------|---|
| Membrane | NBR |
| Merjenje pretoka | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1/2 |
| Odtok kondenzata | Manual |
| Ohišje | Die-cast zinc |
| Posoda | Metal container with viewing tube |
| Serija | variobloc |
| Tesnilo | NBR |
| Vzmet pokrova motorja | POM |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 2 |
| Max. krmilno območje [bar] | 10 |
| Zaslon manometra max. [bar] | 10 |
| Max. vhodni tlak [bar] | 20 |
| Rang filtra [μ m] | 40 |
| A [mm] | 70.0 |
| Max. sobna temperatura [°C] | 80 |
| Max. temperatura medija [°C] | 80 |
| C [mm] | 98.0 |
| B [mm] | 273.0 |
| Pretok [l/min] | 5500 |