

Datum: 03.07.2024



(slika je simbolična)

## Filter-regulator z PC zbir.Vel. 1, G 1/2, 0.5 - 16 bar

Kategorija: [Combined service unit, PC bowl, manual drain](#)  
Šifra: **101093RIE**

### Kratek opis

Combi-service unit with PC container, manual bleeder valve, Size 1, G 1/2, Input pressure max. 16 bar, Control range 0.5 - 16 bar

A filter, pressure regulator and oil-mist lubricator combined in a single device with an extremely compact design.

The pressure setting can be locked by pushing the knob down.

Oil can be filled under pressure.

### Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Manual drain valve
Ohišje	Die-cast zinc
Posoda	Polycarbonate container
Tesnilo	NBR
Vidna kupola	PA
Vzmet pokrova motorja	PA
Min. krmilno območje [bar]	0.5
Velikost	1
Max. krmilno območje [bar]	16
Max. vhodni tlak [bar]	16
Rang filtra [ $\mu$ m]	40
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
A [mm]	65.0
C [mm]	68.5
B [mm]	217.0
Pretok [l/min]	1000