

Datum: 24.08.2024



(slika je simbolična)

Filter-regulator Zašč. kletka Vel. 1, G 1/2, 0.5 - 16 bar

Kategorija: [Combined service unit, PC bowl and bowl guard](#)Šifra: **101103RIE**

Kratek opis

Combi-service unit with PC container and Protective cage,
Size 1, G 1/2, Input pressure max. 16 bar, Control range 0.5
- 16 bar

A filter, pressure regulator and oil-mist lubricator combined
in a single device with an extremely compact design.

The pressure setting can be locked by pushing the knob
down.

Oil can be filled under pressure.

Tehnične Specifikacije

| | |
|---------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p =$ 1 bar |
| Navoj | G 1/2 |
| Odtok kondenzata | Manual drain valve |
| Ohišje | Die-cast zinc Polycarbonate container with protective cage |
| Posoda | NBR |
| Tesnilo | PA |
| Vidna kupola | PA |
| Vzmet pokrova motorja | PA |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 1 |
| Max. krmilno območje [bar] | 16 |
| Max. vhodni tlak [bar] | 16 |
| Rang filtra [μ m] | 40 |
| Max. sobna temperatura [°C] | 50 |
| Max. temperatura medija [°C] | 50 |
| A [mm] | 65.0 |
| C [mm] | 68.5 |
| B [mm] | 217.0 |
| Pretok [l/min] | 1000 |