



(slika je simbolična)

Filter-regulator Zašč. kletka Vel.1,G 1/4, 0.5 - 16 bar

Kategorija: [Combined service unit, PC bowl and bowl guard](#)
Šifra: **101099RIE**

Kratek opis

Combi-service unit with PC container and Protective cage,
Size 1, G 1/4, Input pressure max. 16 bar, Control range 0.5
- 16 bar

A filter, pressure regulator and oil-mist lubricator combined
in a single device with an extremely compact design.

The pressure setting can be locked by pushing the knob
down.

Oil can be filled under pressure.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p =$ 1 bar
Navoj	G 1/4
Odtok kondenzata	Manual drain valve
Ohišje	Die-cast zinc Polycarbonate container with protective cage
Posoda	NBR
Tesnilo	PA
Vidna kupola	PA
Vzmet pokrova motorja	PA
Min. krmilno območje [bar]	0.5
Velikost	1
Max. krmilno območje [bar]	16
Max. vhodni tlak [bar]	16
Rang filtra [μ m]	40
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	50
A [mm]	67.0
C [mm]	68.5
B [mm]	217.0
Pretok [l/min]	1000