



Filter »variobloc« s kovinsko posodo, Velikost 2, G 3/4

Kategorija: [Filter with metal bowl incl. sight glass](#)
Šifra: **125318RIE**

(slika je simbolična)

Kratek opis

Filter »variobloc« with metal container incl. viewing tube, Size 2, G 3/4, Input pressure max. 20 bar, Manual bleeder valve

Centrifugal separators with a sintered filter element. Filtration takes place in a 2-stage process comprising cyclone separation (condensate) and a PE filter element (particles).

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

| | |
|------------------------------|---|
| Merjenje pretoka | At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/4 |
| Odtok kondenzata | Manual |
| Ohišje | Die-cast zinc |
| Posoda | Metal container with viewing tube |
| Serija | variobloc |
| Tesnilo | NBR |
| Velikost | 2 |
| Max. vhodni tlak [bar] | 20 |
| C [mm] | 26.0 |
| Rang filtra [μ m] | 40 |
| A [mm] | 70.0 |
| Max. sobna temperatura [°C] | 80 |
| Max. temperatura medija [°C] | 80 |
| B [mm] | 202.0 |
| Pretok [l/min] | 3500 |